

The listing of the claims will replace all prior versions, and listings, of claims in the application: JC17 Rec'd PCT/PTO 24 MAR 2005

Listing of Claims:

Claim 1 (currently amended). A hydraulic stabilizing device for vehicles, having an actuator that can be acted on in opposite directions, in particular a roll stabilizing device having an actuator which is assigned to an axle of a vehicle and has connection lines opening out on its acted-on sides corresponding to the opposite actuating directions, with a switching device, which can be switched between a direct pass-through position and a crossed-over pass-through position, and, in series with the switching device, a switching apparatus, which can be switched between a pass-through position and a blocking position as its basic position, located in the connection of these connection lines to a pressure source and a pressure reducer, ~~characterized in that~~ wherein the switching apparatus (18) comprises two separate switching valves (20, 21) which are arranged in parallel with one another and of which one switching valve (20) has a blocking position and a direct pass-through position and the other switching valve (21) has a blocking position and a crossed-over pass-through position.

Claim 2 (currently amended). The hydraulic stabilizing device as claimed in claim 1, ~~characterized in that~~ wherein the switching device (17) is formed by a 4/2 way valve.

Claim 3 (currently amended). The hydraulic stabilizing device as claimed in claim 1 ~~or 2, characterized in that~~ wherein the switching valves (20, 21) of the switching apparatus (18) are formed by 4/2 way valves.

Claim 4 (currently amended). The hydraulic stabilizing device as claimed in claim 1 ~~one of the preceding claims, characterized in that~~ wherein the switching device (17) is arranged upstream of the switching apparatus (18).

Claim 5 (currently amended). The hydraulic stabilizing device as claimed in ~~one of claims 1 to 3, characterized in that~~ wherein the switching device (17) is arranged downstream of the switching apparatus (18).

Claim 6 (currently amended). The hydraulic stabilizing device as claimed in claim 1 ~~one of the preceding claims, characterized in that~~ wherein pressure sensors (24, 25) are arranged downstream of the switching apparatus (18) in the lines (22, 23) leading to the actuator.

Claim 7 (currently amended). The hydraulic stabilizing device as claimed in claim 5 ~~or 6, characterized in that~~ wherein the pressure sensors (24, 25) are located between switching apparatus (18) and switching device (17).

Claim 8 (currently amended). The hydraulic stabilizing device as claimed in claim 5 ~~or 6, characterized in that~~ wherein the pressure sensors (24, 25) are located downstream of the switching device (19).